



TOUCH
SCREEN 7"



INTERNET
OF THINGS



WIFI



USB



ETHERNET



PORTABLE DOG TAG & MEDICAL ALER TAG EMBOSSE

The **ME550 DOG TAG** is a portable, fully automatic solution for marking dog tags and medical alert tags and it is currently among the most reliable and easy to use machines on the market. With a 10% increase in production speed, a completely renewed design and new advanced features, the **ME550 DOG TAG** is an advanced heavy-duty desktop solution that can be integrated into any existing factory and office network.

7" color touchscreen display with high resolution

The **ME550 DOG TAG** is equipped with a built-in 7" WVGA LCD touchscreen display with simple and easy to use icon and buttons. The user can access and manage machine functions through a multi-level menu in an easy and intuitive way.

IoT (Internet of Things) remote access and management

- **Web services:** The machine set-up and operations can be entirely managed remotely via the web or through the use of VNC (Virtual Networking Computing) client, using a personal computer or other devices connected to the Customer's network.

- **Data transfer:** Data import/export and the machine updating can be managed from any device connected to the embosser via Ethernet by using the FTP protocol (file transfer protocol).

USB (type A, type B), Ethernet and WiFi

The **ME550 DOG TAG** can be connected to a personal computer, to load data and start production, or to another device, such as keyboard, barcode reader or other if needed.

The **ME550 DOG TAG** is equipped with removable input hoppers for easy change between medical alert and dog tags. The unit is truly portable due to the light weight – only 26 kg / 57.3 lbs – and, in addition, to a sturdy case and an easy to carry built in handle (optional).

The **ME550 DOG TAG** has been designed as the ideal, no hassle dog tag machine for low to medium production volumes.



USED BY

- POWER & UTILITY COMPANIES
- U.S. MILITARY
- INDUSTRIAL MANUFACTURERS



IDEAL FOR

- FULLY AUTOMATIC INSTANT ISSUANCE
- ISSUANCE OF DOG TAGS & MEDICAL ALERT TAGS IN ALL ENVIRONMENTS

FEATURES AND SPECIFICATIONS

MODEL NAME ME550 DOG TAG

PLATE AND FEEDER

Dimensions Dog tag: 52 x 29 mm - 2.05 x 1.14 in (WxH)
Medical alert tag: 57 x 32 mm - 2.24 x 1.26 in (WxH)



dog tag



medical alert tag

Materials Aluminum, stainless steel
Thickness Dog tags: 0,3556 ÷ 0,4572 mm - 0.014 ÷ 0.018 in
Medical alert tags: 0,6604 ÷ 0,8128 mm - 0.026 ÷ 0.032 in
Input hopper Up to 120 plates capacity (0,4 mm - 0.0157 in)
Output hopper External collection tray

MARKING

Technology Embossing or debossing
Wheel capacity 60 slots
Type set Simplex 2, Elite Dog Tag, Block USA, Block 5, OCRB1
Embossing area See picture. 5 lines / 15 characters (elite 328 Dog Tag)
Performance 150 tags per hour based on 45 characters

COMMUNICATION AND SOFTWARE

Interface USB 2.0 port (device and host), Ethernet, WiFi
Software Linux based self enclosed software
PowerTag PC application proprietary software Windows 7/8/10
PowerTag USB on USB key for multiple use
Protocol Multiembosser
Optional: Cim, Xon-Xoff, Stored Format default, Stored Format Selected and Pound-Pound

HARDWARE

System CPU Arm Cortex-A8 / RAM 256 MB, with flash-disk and file system Linux O.S. based
Power supply Universal switching power supply 100-240 volts; 50 or 60 hz
Power consumption 300 Watt max
Operating environment Temperature: 5°÷ 40°c / 41°÷104° F, relative humidity 30% ÷ 90%

VARIOUS


Others Built in touch screen 7", multi-language user interface management: English, Spanish, Italian
Innovative embedded software up-grade system thru pen drive and web server
Interchangeable input hopper for easy charge and discharge of medical alert & dog tags
Machine configuration protected by password for high security and data protection
Easy to carry handle, no packaging required

CERTIFICATIONS

UL, FCC, CE, ROHS




EMBOSSING AREA



Dashed area not usable height
1 ÷ 3,5 mm - 0.04 ÷ 0.137 in



DIMENSION



WEIGHT

26 Kg / 57.3 lbs



SOFTWARE

power tag
LITE
optional
power tag
EVO